Buckleberry Limited

screen print supply company

... the complete solution for screen printers

SAFETY DATA SHEET

B – WASH WHITE

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name B-Wash White

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

As a wash-off solvent in printing processes.

1.3. Details of the supplier of the safety data sheet

Supplier

Buckleberry Ltd Buckleberry House 9 Hales Road Leeds LS12 4PL 0113 2797779 (08:00-16:30) 0113 2797770 sales@buckleberry.co.uk

1.4. Emergency telephone number

Emergency telephone Buckleberry Ltd 0113 2797779 (08:00-16:30)

National emergency telephone 999 / 112 number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Flam. Liq. 3 - H226

Health hazards

Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC)

Xn; R65, R20. Xi; R36/37/38. N; R51/53. R10, R67, R66

Human health

In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. The liquid is irritating to eyes and skin. Organic solvents may be absorbed into the body by inhalation and ingestion. Product has a defatting effect on skin. Vapours/aerosol spray may irritate the respiratory system.

Environmental

The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical

Heating may generate flammable vapours. Vapours may form explosive mixtures with air.

2.2. Label elements

Pictogram	
. Ne	
<u>(73</u>	
Signal word	Danger
Hazard statements	
	H226 Flammable liquid and vapour.
	H304 May be fatal if swallowed and enters airways.
	H315 Causes skin irritation.
	H319 Causes serious eye irritation.
	H332 Harmful if inhaled.
	H335 May cause respiratory irritation.
	H336 May cause drowsiness or dizziness.
	H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	
	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P261 Avoid breathing vapour/spray.
	P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
	P331 Do NOT induce vomiting.
	P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
	P501 Dispose of contents/container in accordance with national regulations.
Supplemental label information	tion
	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	Hydrocarbons, C9, aromatics, CYCLOHEXANONE, 2-BUTOXYETHANOL
Detergent labelling	≥ 30% aromatic hydrocarbons
Supplementary precautiona	ry statements

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C9, aromatics		60-100%
CAS number: — EC number: 918-668-5 RE	ACH registration number: 01-2119455851-35-XXXX	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	Xn; R65. Xi; R37. N; R51/53. R10, R67, R66	
STOT SE 3 - H335, H336		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		
CYCLOHEXANONE		10-30%
CAS number: 108-94-1 EC number: 203-631-	1 REACH registration number: 01-2119453616-35-XXX	<
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	Xn; R20. R10	
Acute Tox. 4 - H332		

2-BUT	OXYETH	ANOL	

2-BUTOXYETHANOL			10-30%
CAS number: 111-76-2	EC number: 203-905-0	REACH registration number: 01-2119475108-36-XXXX	X
Classification		Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H302		Xn; R20/21/22. Xi; R36/38	
Acute Tox. 4 - H312			
Acute Tox. 4 - H332			
Skin Irrit. 2 - H315			
Eye Irrit. 2 - H319			
The Full Text for all R-Phr	ases and Hazard Stateme	nts are Displayed in Section 16.	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Move affected person to fresh air at once. Keep affected person warm and at rest. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration.

Ingestion

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention immediately. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

Skin contact

Remove affected person from source of contamination. Take off immediately all contaminated clothing and wash it before reuse. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

Eve contact

Remove any contact lenses and open evelids wide apart. Wash with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Harmful by inhalation. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death. Upper respiratory irritation.

Ingestion

Diarrhoea. May cause nausea, headache, dizziness and intoxication. Aspiration hazard if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact

This product is rapidly absorbed through the skin and may cause symptoms similar to those of ingestion. Skin irritation. Repeated exposure may cause skin dryness or cracking.

Eye contact

Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

No specific recommendations. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with the following media: Carbon dioxide (CO2). Alcohol-resistant foam. Dry chemicals, sand, dolomite etc.

Unsuitable extinguishing media

Do not use water, if avoidable.

5.2. Special hazards arising from the substance or mixture

Specific hazards

The product is flammable. Heating may generate flammable vapours. No unusual fire or explosion hazards noted.

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Containers close to fire should be removed or cooled with water. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Evacuate area. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions

Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid contact with skin or inhalation of spillage, dust or vapour. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections

For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Use approved respirator if air contamination is above an acceptable level. Contaminated rags and cloths must be put in fireproof containers for disposal. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C9, aromatics

Long-term exposure limit (8-hour TWA): SUP 19 ppm 100 mg/m3

CYCLOHEXANONE

Long-term exposure limit (8-hour TWA): WEL 10 ppm 41 mg/m3 Short-term exposure limit (15-minute): WEL 20 ppm 82 mg/m3

Sk

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m3 Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m3 Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

	Hydrocarbons, C9, aromatics
DNEL	Industry - Dermal; Long term systemic effects: 25 mg/kg/day Industry - Inhalation; Long term systemic effects: 150 mg/m3
	2-BUTOXYETHANOL (CAS: 111-76-2)
DNEL	Industry - Dermal; Short term systemic effects: 89 mg/kg/day Industry - Inhalation; Short term systemic effects: 135 ppm Industry - Inhalation; Short term local effects: 50 ppm Industry - Dermal; Long term systemic effects: 75 mg/kg/day Industry - Inhalation; Long term systemic effects: 20 ppm
PNEC	- Fresh water; 8.8 mg/l - Marine water; 0.88 mg/l - STP; 463 mg/l - Sediment (Freshwater); 34.6 mg/kg - Sediment (Marinewater); 3.46 mg/kg - Soil; 2.8 mg/kg

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Use explosion-proof electrical, ventilating and lighting equipment.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. Do not smoke in work area. Do not eat, drink or smoke when using this product.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Liquid.

Colour

Colourless to pale yellow.

Odour

aromatic hydrocarbons

Odour threshold

No information available.

pН

Not applicable.

Melting point

Not applicable.

Initial boiling point and range 140-200°C @ 760 mm Hg

Flash point >35°C TCC (Tag closed cup).

Evaporation rate No information available.

Evaporation factor No information available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits Lower flammable/explosive limit: 0.7 g/100 g Upper flammable/explosive limit: 10.6 g/100 g

Vapour pressure >0.01 kPa @ 20°C

Vapour density >1

Relative density ~ 0.9 @ 20°C

Bulk density Not applicable.

Solubility(ies)

Limited water solubility.

Partition coefficient No information available.

Auto-ignition temperature >240°C

Decomposition Temperature No information available.

Viscosity Kinematic viscosity ≤ 20.5 mm²/s.

Explosive properties

Not applicable.

Oxidising properties

Not applicable.

Comments

Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

9.2. Other information

Volatile organic compound

This product contains a maximum VOC content of 892 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability

Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Will not polymerise.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid

Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 10,301.10935024

Acute toxicity - dermal

ATE dermal (mg/kg) 8716.32329635

Acute toxicity - inhalation

ATE inhalation (gases ppm) 17347.72552043

ATE inhalation (vapours mg/l) 42.40555127

ATE inhalation (dusts/mists mg/l) 5.78257517

Skin corrosion/irritation

Animal data Slightly irritating.

<u>Serious eye damage/irritation</u> Slightly irritating.

Respiratory sensitisation

Based on available data the classification criteria are not met.

Skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro

Does not contain any substances known to be mutagenic.

Carcinogenicity

Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility

Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure

A single exposure may cause the following adverse effects: Gas or vapour may irritate the respiratory system. Drowsiness, dizziness, disorientation, vertigo.

Target organs

Central nervous system Respiratory system, lungs Brain

Specific target organ toxicity - repeated exposure

STOT - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Inhalation

Harmful by inhalation. The product contains organic solvents. Overexposure may depress the central nervous system, causing dizziness and intoxication. Irritating to respiratory system.

Ingestion

Harmful: may cause lung damage if swallowed. May cause discomfort if swallowed. May cause nausea, headache, dizziness and intoxication.

Skin contact

Irritating to skin. Contains components which may penetrate the skin. Repeated exposure may cause skin dryness or cracking.

Eye contact

Irritating to eyes.

Route of entry

Inhalation Skin absorption Ingestion. Skin and/or eye contact

Target organs

Central nervous system Brain Eyes Respiratory system, lungs Skin

Medical symptoms

Headache. Fatigue. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Unconsciousness, possibly death. Diarrhoea. Dryness and/or cracking. Irritation of eyes and mucous membranes. Irritation of nose, throat and airway. Skin irritation.

SECTION 12: Ecological Information

Ecotoxicity

The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Acute toxicity - fish

Not known.

Acute toxicity - aquatic invertebrates

Not known.

Acute toxicity - aquatic plants

Not known.

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Acute toxicity - fish LC₅₀, 96 hours: 9.2 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 3.2 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 2.9 mg/l, Algae

<u>Chronic aquatic toxicity</u> NOEC 0.01 < NOEC ≤ 0.1

Chronic toxicity - aquatic invertebrates

, 21 days: 2.14 mg/m³, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability

This cleaning preparation does not contain any surfactants. The product is readily biodegradable.

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Persistence and degradability

The product is readily biodegradable.

12.3. Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient

No information available.

12.4. Mobility in soil

Mobility

The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is partly soluble in water and may spread in the aquatic environment.

12.5. Results of PBT and vPvB assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids may self-ignite after use and should be stored in designated fireproof containers with tight-fitting, self-closing lids. When handling waste, the safety precautions applying to handling of the product should be considered.

SECTION 14: Transport information

<u>14.1. UN number</u>	
UN No. (ADR/RID)	1210
UN No. (IMDG)	1210
UN No. (ICAO)	1210
UN No. (ADN)	1210
14.2. UN proper shipping	name
Proper shipping name (ADR/RID)	PRINTING INK RELATED MATERIAL
Proper shipping name (IN	IDG) PRINTING INK RELATED MATERIAL
Proper shipping name (IC	CAO) PRINTING INK RELATED MATERIAL
Proper shipping name (A	DN) PRINTING INK RELATED MATERIAL
14.3. Transport hazard cla	ass(es)
ADR/RID class	3
ADR/RID classification co	de F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3
Transport labels	
14.4. Packing group	
ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III
ADN packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



Yes.

14.6. Special precautions for user

EmS	F-E, S-D
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)
Limited Quantity Value:	5 Litres

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Known

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance

Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and sources for data

Material Safety Data Sheet, Misc. manufacturers.

Classification procedures according to Regulation (EC) 1272/2008

: Calculation method., On basis of test data.

Revision comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

_	
Issued by	J Waterfield
Revision date	18/09/2014
Revision	3.0
Supersedes date	20/08/2009
SDS number	20963
Risk phrases in full	
	R10 Flammable.
	R20 Harmful by inhalation.
	R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
	R36/37/38 Irritating to eyes, respiratory system and skin.
	R36/38 Irritating to eyes and skin.
	R37 Irritating to respiratory system.
	R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R65 Harmful: may cause lung damage if swallowed.
	R66 Repeated exposure may cause skin dryness or cracking.
	R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.